

Workshop Essentials 2024 Q3/Q4

Winntec Workshop Essentials Contents





Reaching new Heights

We manufacture, develop and supply top-quality, efficient, and dependable automotive workshop essentials that are competitively priced and supported by exceptional customer service and support.

In the coming years, our primary focus is on lifting, handling, and transportation safety & ergonomics.

We understand the challenges mechanics face, both in workshops and on the road. As the quantity of heavy items (both vehicles and their commodities) increases, we believe it is our responsibility to supply cost-effective solutions that will save time and significantly reduce any risk.

Our second focus is ease of use.

Our products are known to be operator-friendly and excel in ergonomics.

Winntec products are designed & manufactured in compliance with NEN-EN 1494:2001+A1:2008 C € \u00e4.



05.

Wheel Handling Equipment By Winntec

Y471147 HD Classic - Smart Cart Ø 76 cm



Y471148 HD Dominator - Smart Cart Ø 83 cm

Our new Smart Cart with PATENTED LOADSHIFT TILTING SYSTEM, suits tire techs that transport tires and wheel sets all day long in and around the shop and at racetracks. It picks up even bigger wheels than its predecessor, while its integrated kick pedal ensures a quick release of 'the load'. The redesigned, stronger, sleeker arms in stainless guarantee a perfect catch and grip of the heaviest wheels and wheelsets. Your Dominator comes with a bracket set to easily carry a Smart Disc along.

Specifications		Main Features
Height =	1385 mm	• REQUIRES 3x LESS EFFORT TO T
Width =	610 mm	BY MAKING USE OF LOADSHIFT™ TECHNOLO
Depth =	695 mm	3+7 YEARS WARRANTY (upon active Auto open/close stainless grippe
Range Ø =	up to 83 cm	 Height-adjustable top plate with Foot Control Bar for better load r
Alterally	220 kg	Spring-operated kick pedal
KG	23.3 kg	 Handles tires and wheel assemble

Y471148EXT - Extender Kit

OPTIONAL bolt-on/off extender with rubber grips to increase the carrying capacity of the DOMINATOR to 8 tires. Easy installation and removal. Highly recommended for those who transport large stacks of tires.

Y471105 - Wheel Dolly

Remove wheel assemblies quickly & efficiently. Its ergonomic design reduces the chance of (back strain) injuries. Equipped with adjustable extended rollers and rubber wheels with a steel core.

Specificatio	ns	Mai
Frame size	700*1000 mm	• QU
11 ¹⁰ 1	220 kg	• Ex
КG	15 kg	

in Features

- UICK DETACH HANDLE
- tended rollers 290 mm

Y471106 - Truck Wheel Dolly

This lightweight, portable dolly with hydraulic unit to ensure precise positioning, allows the operator to work on a very short distance from the vehicle, perfect for road assistance service work. Its shock absorbing casters ensure a smooth ride from and to the hub.

Specificatio	ns	Main Features			
Frame size	900*450*310 mm	CARRY HANDLE & BELT			
AN	160 kg	Maximum mobility			
К	29 kg	 Fast positioning 			



Y472280 - Wheel Assist NXT

Quickly and easily remove and replace wheels while at an ergonomically correct position. It allows the operator to lift and lower wheel assemblies from floor to shoulder height. Trigger control ensures variable speed. Operates with Makita/Milwaukee batteries.







Our Smart Carts and Wheel Assists form a great team and work in line with each other.

Lifting Equipment Floor Jacks

When we founded Winntec in 2002, we rebuild the hydraulic floor jack from scratch. The result was an innovative, operator-friendly, and servicable design that combined European and American features and functionality.

Today we have the most complete hydraulic jack range in the game, with capacities ranging from 1.35 to 32 tons.

TURBOLIFT and 2-SPEED LOWERING are two of many technologies we implemented since then. What started out as distinguishing factors have now become standard features for almost all of our jacks. Their quality, safety and ease of use are - and remain - at the heart of our operations.



Model	Min H.	Max H.	Size (W x L)	Alust	К
Y411350	80	375	236 x 501	1.35 T	10 kg
M411355	90	360	247 x 481	1.5 T	14.2 kg
Y411202	86	418	282 x 625	2 T	22 kg
Y420222	75	500	350 x 705	2 T	42 kg
Y420250	75	510	343 x 686	2 T	32,5 kg
Y420330	120	450	344 x 618	3 T (US)	31 kg
Y420333	76	503	346 x 672	3 T	37 kg
Y420336	95	540	350 x 688	3.6 T	38.5 kg

specifications	
1in. H. =	80 mm
1ax H. =	375 mm
Vidth =	236 mm
.ength =	501 mm
all the second s	1,35 T
KG	10 kg

90 mm
360 mm
247 mm
481 mm
1,5 T
14 kg

Specification	Specifications			
Min. H. =	86 mm			
Max H. =	418 mm			
Width =	282 mm			
Length =	625 mm			
A Call	2 T			
KG	22 kg			





07

Y420250 - Ultra Low Floor Jack 27

to the underside of the chassis, are standard features.

Main Features

- 2-SPEED LOWERING
- TURBO LIFT
- Rubber saddle pad · PU wheels

Comes with heat-treated chromed pump pistons and chromed main ram. Like all our other jacks, it is equipped with cardan transmission, which makes the jack very smoothly maneuverable.

Ultra low profile design combined with TURBO LIFTER technology. The jack starts at 3in and

reaches an impressive 510mm at maximum height. The PU wheels minimize noise and

potential (showroom) floor damage. A rubber grip and saddle pad, which prevents damage

Specifications Min. H. = 75 mm Max H. = 510 mm Width = 343 mm Length = 686 mm Alasyli 2 T KG 32,5 kg





Y420222 - Ultra Low Floor Jack with Integrated Jack Stand Function 2T

This ultra-low floor jack (75 mm) is equipped with an integrated jackstand function and has a maximum lifting height of 500 mm. Hold-to-run control. The poly-urethane wheels are noise reducing and prevent damage to floors. The saddle is covered by a rubber pad that prevents damage to the underside of the chassis. The handle is covered by a handle bumper that prevents damage to the car.

Specifications	
Min. H =	75 mm
Max. H =	500 mm
Width =	350 mm
Length =	705 mm
ANEN	2T
К	42 kg

Main Features

INTEGRATED JACKSTAND FUNCTION

FIT!

- 2-SPEED LOWERING TURBO LIFT
- Hard-chromed ram and pistons
- Auto-lock
- Rubber pad











Specifications		Main Feat
Min. H. =	120 mm	 2-SPEED LO TURBO LIFT
Max H. =	450 mm	Rubber sadd
Width =	344 mm	PU wheels
Length =	618 mm	
NS ^{II}	3 T (US)	(
KG	31 kg	

pecifications	\$
lin. H. =	76 mm
lax H. =	503 mm
/idth =	346 mm
ength =	672 mm
e ^N	3 T
G	37 kg

pecifications	
lin. H. =	95 mm
lax H. =	540 mm
/idth =	350 mm
ength =	687 mm
etter and a second s	3,6 T
G	38,5 kg







© Copyright Top Gear

It is no wonder that we have 500.000+ active lifting devices in the field.



Lifting Equipment Long Chassis Jacks


Long Chassis Jacks 2 - 10T

Our Long Chassis Jacks are built for heavy duty lifting. They come with foot pedals for quick lifting and ergonomically designed handles with a release button to gradually lower the jack. Furthermore, these jacks are equipped with an automatic overload safety valve and durable swivel castors.


Jack dimensions

A = Min. Height (mm) B = Max. Height (mm) C = Width (mm) D = Length (mm) E = Height (mm)

Model	А	В	С	D	Е	Alasylt	кд
Y420200	138	800	396	1310	1285	2 T	58
Y420301	130	600	325	1400	1330	3 T	65
Y420500	150	680	366	1505	1345	5 T	90
Y421000	160	680	485	1635	1355	10 T	145







Lifting Equipment Bottle Jacks

Bottle Jacks 2-30T

Versatile for use in a large variety of applications: pushing, bending, pressing or straightening. The full range comes with cast iron bases, polished main rams and a solid, chromed pump linkage. These jacks are tested to the latest European standards, have overload protection and can be used in both horizontal and vertical positions. All models (except Y413000 & Y411000) have a twist top for precise height adjustments.

The telescopic Y411000 comes with two extensions (45 mm & 6 mm), internally machined oil passages, smooth bearing surfaces and close tolerances.



Jack dimensions

Model	Base plate (mm)	Min H. (mm)	Lifting H. (mm)	Adjust H. (mm)	Max H. (mm)	AVENT	🦾 (kg)
Y410200	96 x 93	158	90	60	308	2 T	2.3
Y410400	112 x 104	180	110	60	350	4 T	3.3
Y410600	116 x 116	197	125	60	382	6 T	4.4
Y410800	120 x 120	205	125	60	390	8 T	5.4
Y411000	180 x 118	120	100	-	260	10 T	6.4
Y411200	140 x 135	214	125	60	399	12 T	7.2
Y411500	140 x 140	225	140	60	425	16 T	8.3
Y412000	155 x 140	244	145	60	449	20 T	10.5
Y412001	155 x 140	190	90	60	340	20 T	9
Y413000	175 x 160	285	180	-	465	30 T	14.6








Y412001



Y411000

Telescopic model 10T

Y413000



Lifting Equipment Air Bottle Jacks

Y432020 - Air Bottle Jack 20T

Among the toughest in the market. Equipped with an air regulator, a chrome ram, a welded base, and return springs so that these jacks will keep on working no matter the job. Each unit is hand-tested before shipping to guarantee maximum reliability.

Main Features

- WELDED BASE
- Extension screw
- High speed air motor
- Chromed ram

Y432021 - Low Profile Air Bottle Jack 20T

This unit includes a welded base to prolong service. Chrome main ram and aluminum air motor guarantee optimum lifetime. Air filter and air regulator connected to hose, included. Does not offer a manually operated pump.

Main Features

- WELDED BASE
- Extension screw
- High speed air motor
- Chromed ram

Y432021 - Air Bottle Jack On Trolley 20T

This model features a specially heat treated cylinder wall and chrome piston, ensuring premium performance and durability. Can be stored vertically.

Main Features

- WELDED BASE
- Can be stored vertically
- High speed air motor
- Chromed ram

Model	Base plate (mm)	Min H. (mm)	Lifting H. (mm)	Adjust H. (mm)	Max H. (mm)	Alasylt	kg (kg)
Y432021	180 x 115	148	66.6	45	260	20 T	9
Y432020	220 x 175	245	150	80	475	20 T	16.5
Y432003	300 x 150	253	150	80	483	20 T	25.7






Lifting Equipment Air Hydraulic Jacks

Y432024 - Single Stage Air Service Jack 20T

This single stage air service jack delivers a massive 24 Ton of power and comes with premium interior hydraulic and pneumatic components. It is designed to meet and exceed expectations of a quality jack at a very competitive market value. The controller allows for the jack to ascend and descend with air. No more relatively unsafe, manual descending of heavy trucks! This Y432024 comes with 3 extensions (20mm, 50mm & 100mm) and is equipped with an 85mm extension screw. The heavy duty wheels have been designed for daily use.



Y432032 - Telescopic Air Service Jack 20T

Dual stage air service jack with a low entrance height of just 150mm and hard chromed piston. It's 32/16 Ton capacity and compact dimensions, make this jack ideal for both workshop and road assistance duty. Air-controlled ascend and descend ensures maximum safety. Comes with 2 extensions (45mm & 100mm). As an option we offer a 260mm extension.

Main Features

HARD CHROMED PISTONS

- Pneumatic descend
- Dead-man control

GT260MM-EXT

260mm extension for Y432032

Main Features

HARD CHROMED PISTON

- Pneumatic descend
- Dead-man control Extension screw

AIR CONTROLLED T DESCENT LOW **MEARA**

Lifting Equipment Balloon Jacks

Y422002 - Pneumatic Balloon Jack 2T

Lifts extremely fast and can easily be placed on a car lift. A safety valve prevents from over inflation, while the internal telescopic stabilizer (ASTM-513 steel) provides stability.

Main Features

- IDEAL ON 4 POST LIFT
- 2-Stage Low Profile Balloon Jack
- Internal telescopic stabilizer
- Turn saddle for precise height control
- Safety valve



Specifications Y422002					
A =	300 mm	A ¹ =	360 mm		T
B =	125 mm	B1=	185 mm		I F
D =	400 mm			A ¹	
1001	2 T				
KG	14,8 kg				

Lifting Equipment Forklift Jack

Y454000 - Forklift & Tractor Jack 4/5T

Forklift jack with dual lifting points (4/5T), 2-Speed Lowering, chromed ram and chromed pump piston. Lower, extended arm is only 65mm for easy access under forklift trucks. The upright piston at 416mm is ideal for lifting tractors and farm machinery. Hydraulic lift 355mm on forklift arm and 350mm on upright piston


Main Features

- WELDED BASE
- 2-Position lift pad
- · High-strength frame work


Specification	s
Max. Height	425 mm
Min. Height	65 mm
ANS HE	4/5T
КС	45 kg

Y422012 - Pneumatic Balloon Jack 2T

Our Y422002 equipped with a handle and wheels for easy positioning under the vehicle.









Lifting Equipment Scissor Lifts

Y475054 - Ultra Low Scissor Lift 3.5T

AUTOMATIC BALANCING

Self-lock function of dual circuit hydraulic system

Specifications		Y475054		
Width	480 mm	Operation pressure	0.6 - 0.8 Mpa	4
Length	1400 mm	Rated voltage	25 Mpa	
Min. H Max. H.	105-1000 mm	Power voltage	230 V	
ANT	3500 kg	Motor power	2.2 KW	
KG	690 kg	Lifting time	50 - 60 sec	

Y475230/400 - Ultra Low Scissor Lift 3.2T

• EXTEND TO 78.75" WHICH SUITS MOST CARS AND SUV'S

• Automatic balancing & self-lock function of dual circuit hydraulic system

Specifications		Y475230 - Y475400		
Width	585 mm	Operation pressure	0.6 - 0.8 Mpa	
Length	1460 mm	Rated voltage	25 Mpa	
Min. H Max. H.	105-1900 mm	Power voltage	230 / 400 V	
A Call	3200 kg	Motor power	2.2 KW	
KG	810 kg	Lifting time	50 - 60 sec	

Y475051 - IN-SYNCH2 2.5T

Open undercarriage access, portable and easy to maneuver. Smooth perfectly in-sync lifting and lowering ensured by our patented valve blocks. Quick-connect fittings make it easy to assemble/disassemble.

TECHNICAL DATA	
Frame width	300 mm
Frame length (lowest position)	1910 mm
Min. H Max. H.	85 - 455 mm
Lifting point spread (Min.)	800 mm
Lifting point spread (Max.)	1320 mm
Weight	95 kg

Y475052 - RAZZ01 1.8T

Mini lift with mechanical safety lock. Extremely versatile lift, operated with an industrial, airhydraulic footpump, which allows you to quickly lift and support any small/large car, vans and SUVs.

TECHNICAL DATA

Length (arms withdrawn)	1120 mm
Length (arms extended)	1910 mm
Width	400 mm
Min. H Max. H.	110 mm - 630 mm
Weight	113 kg




Workshop Equipment Crane, Gearbox & Engine Service

Workshop Equipment Industrial Presses

Y440104 - Foldable Crane 17

Constructed from heavy gauge welded square tubular steel. The 2-speed hydraulic pump with chromed ram rotates up to 135 degrees ensuring the optimal working position. Fine adjustment lowering handle with dead man's control, nylon wheels avoid floor damage, 3 pre-set positions for lifting and easy to maneuver.



Y451555 – Transmission Jack 500KG

Its superior stability and efficient pump system ensure a fast and precise approach. Suitable for installing and dismantling gearboxes, engines & couplings.



Y440105 - Engine Leveler

Drop-forged steel engine leveler (550 kg) with heat-treated fully adjustable chains. Comes with two 1000 mm load chains.



Y450102 - Engine Stand 500KG

Adjustable arms ensure ease and speed. Rotate 360° with the handle. A locking pin secures in any of the 8 positions.

Specifications 860 mm 750 mm 760 mm 450 kg 19 kg

SHOP UST-H/

Industrial Presses 15 - 50T

Our presses with welded frame are suited for standard pressing, bending, bonding and straightening jobs. Essential for the removal/installation of universal joints, bearings, pulleys, and wrist pins. Includes 2 V-blocks for easy and secure positioning.

Y461520 - Press 20T Y461533 - Press 30T • 2-SPEED HAND PUMP • 2-SPEED HAND PUMP Sliding cilinder Movable cylinder (left-right) Pneumatic foot operation Y461516 - Press 157 Model Height (n BENCH MODEL • 2-SPEED HAND PUMP Y461516 1015 Y461520 1830 Y461533 1850 Y461555 1850

Accessories







- 2-SPEED HAND PUMP
- Movable cylinder (left-right)
- · Pneumatic foot operation



nm)	Depth (mm)	Width (mm)	ANGIN	К
	134	678	15 T	57,5
	540	850	20 T	101
	540	840	30 T	137
	650	1080	50 T	244



Y461533-PS - Punch Set Y4615XX-PC - Protective Cover







Both our Smart Carts are motorsport's 1st choice because of their ruggedness and ease of use.



Workshop Equipment Jack Stands



Y450350 - Fast Lock Jack Block 3.5T

Your new must-have for any job project. This clever device is a valuable addition to your workshop because it does more than just support your floor jack - it **replaces your jack stand**! It works perfectly with most floor jacks, but is especially useful for lifting electric vehicles (EVs). With its impressive adjustability from 217 mm to 352 mm, it adapts to different vehicle heights. Installation is quick and easy, with a spring mechanism for hassle-free use. For extra security, use the included safety pin and you're ready to work on your vehicle, safely.

Specificatio	ns		
Min. H =	217 mm	MUCT	
1ax. H =	352 mm		VABO350
112 ¹¹	3,5 T	"INVE	B.ST MEAVY DUTY BERIED I WINNTEG.N
KG	1,7 kg		$\overline{\mathbf{O}}$







Y450301 - Jack Stand Ratchet Type 3T

RATCHET TYPE
AUTOMATIC LOCKING
Carrying handle

Y452300 - Jack Stand Pin Type 3T

- PIN TYPE
- LARGE PU SUPPORT PAD



Y452330 - Jack Stand Pin Type 3T

- PIN TYPE
- LOW PROFILE
- 4" REPLACABLE PU SADDLE PAD
- · Base with extra big foot pads for increased stability





Y452600 - Jack Stand Pin Type 6T

- PIN TYPE
- LARGE PU SUPPORT PAD





Workshop Equipment Jack Stands for Truck

Y451205 - Low Profile Jack Stand SET 12T

Low profile jack stand with handle and wheels for easy positioning under the vehicle. The pin type support column adjusts to 5 different height positions. A 8.7in square base secures and stabilizes load.

Main Features

- PIN TYPE
- Low profile handle
- Nylon wheels



Heavy duty, welded, wheeled jack stand set with detachable handle. Multi-angle handle sockets ensure easy storage and safe positioning under the vehicle.

Main Features

- PIN TYPE
- Nylon wheels

Y451206 - High Reach Jack Stand 12T

Heavy duty, high reach welded jack stand with detachable handle, multi-angle handle socket and wheels for easy positioning under the vehicle.

Main Features

- PIN TYPE
- Nylon wheels

Model	Min H. (mm)	Max H. (mm)	W	L	Ø(mm)	ANT	KG
Y450301	305	450	185	209	-	3 T	7
Y452300	322	465	-	-	254	3 T	5,2
Y452330	300	451	279,5	-	310	3 T	9
Y451600	395	625	263	293	-	6 T	13,8
Y452600	404	604	-	-	341	6 T	11,2
Y451205	302	450	280	220	-	12 T	20
Y451206	601	971	423	370	341	12 T	29,2
Y452205	402	575	333	280	-	22 T	42,4




NEVER

SAFETY



Workshop Equipment Miscellaneous




Y471180 - Wheel Removal Kit 10T

This kit eliminates one of the most dangerous jobs within the tire service industry: WHEEL REMOVAL! Alloy and light steel wheels are often frozen (glued) to the vehicle.

This ready-to-use kit includes a case, cylinder, pump, hose and a variation of adaptors to be installed depending on the space between the wheel and the chassis of the vehicle. With 10 Ton of hydraulic power and manual control of the foot pump, it becomes a safe and quick job to press the oxidized wheel from the vehicle.

Main Features



Metal case



Y4781107 - Single Acting Cylinder 42-52mm 10T

Made out of high-strength alloy steel for maximum safety and durability. Unique heavy duty spring ensures fast piston return. Equipped with industrial 3/8-18NPT connections.



Workshop Equipment Miscellaneous

Y471150 - Air Hydraulic Pump 1600cc

For use with a variety of rams, presses and hydraulic tools operating up to 700bar/10,000 psi. Air exhaust muffler for quiet operation. Aluminum housing. Two stage release mechanism; pump, hold or release with pedal control.

Air inlet: 1/4 Air outlet: 3/8 Working pressure: 6-10 bar Weight: 7,9 kg

Y471120 - Hydraulic Combi Bead Breaker 57

Designed to work on all single, two and three pieces 2-5-10 hole budds, 7.50x16s and all tubeless tire/rims. Includes 3 claws. Working range up to 120mm. Self-retracting. Durable anti-corrosive finish.

Y4781155 - Single Acting 2-Speed 900cc 70 Mpa

Light weight, high flow industrial pump with baked enamel finish to increase corrosion resistance. The compact design ensures efficient storage and transportation. Less handle effort to minimize operator's fatigue. Internal pressure relief valve prevents from overload situation.

Industrial 3/8-18NPT outlet. Weight: 6,8 kg

Y478205 - Hose Assembly 2.5m

Compatible with Y471150 and Winntec Bead Breaker model Y471120

Y491110 - Mechanic Gloves M - L - XL

A sturdy glove with protectors for professional work in the workshop.

Main Features

- IMPACT PROTECTION
- Slip free silicone grip
- Double stitched
- Industrial book and loop Machine washable



Y491310 - Precision Gloves L - XL

Perfect for a variety of automotive service jobs that demand a 'fine touch'.

Main Features

- FINE TOUCH
- Anti Slip
- Breathable stretch
- Abrasion resistant
- Terrycloth thumb
- Touch screen proof



Winntec JTM Series Jack The Mech

Designed for the pro - available to all

Winntec's Jack The Mech products are renowned for their high quality and durable construction. They are simple to use and adaptable to users with different degrees of experience, making them a reliable choice for professionals and enthusiasts alike.

Introduced in 2022, 20 years after the founding of Winntec, the Jack the Mech range is characterised by its focus on home tinkerers and professionals alike.

















JTM200010 - Mobile Energy & Air

This mobile battery booster is an indispensable tool for your boat, motorhome, caravan or car. It is also an indeal product for car dealers to be used daily in your workshop, showroom or car park.



Main features

- START BOOSTER 2000A
- COMPRESSOR auto-start-stop 10 bar / 145 PSI
- High capacity power bank 55.5 wh
- Multifunctional LED light

JTM400000 - Detailing seat

The ideal addition to any garage or detailer! Perfect for precise detailing of wheels, tires, exhaust tips, and more, or for use in paint repair and polishing of side panels, bumpers, and lights!

Main features

- CARBON STEEL INNER FRAMING
- Premium swivel casters with 2 locks
- Cradle style seating with onboard storage
- Comfortable height

JTM101224 - Mobile Energy

This 12/24V start booster offers a massive capacity of 10.000A and is an indispensable tool for daily use by roadside service mechanics. Prior to a start attempt, the clampsensors warn you when they measure resistance.

Main features

- START BOOSTER 10.000A 12V / 5.000A 24V
- Multifunctional LED light
- Multiple safety functions integrated

Liftpads **Dedicated Pads**



Y490020 – Liftpad S

LIFTPAD helps to lift safely & reduces the risk of damaging your vehicle's chassis and lifting point! The pad has a 75mm diameter slot that is 15mm deep for compatibility with most brand-specific adapters. Fits most floor jacks, perfect fit guaranteed with our: Y411350 & M411355.

Main Features

- UNIVERSAL FIT
- PFAS & PAHS FREE
- Avoids frame rail damages
- · Avoids lift point deformation



Model	Y490000	Y490010EV	Y490020
Topø=	112 mm	112 mm	110 mm
Height =	43 mm	20 mm	43 mm
Base slot ø =	92 mm	92 mm	80 mm
Base slot 2 ø =	104 mm	104 mm	-
Base slot 3 ø =	106 mm	106 mm	-
Base slot 4 ø =	118 mm	118 mm	-
X-groove =	10/13 mm	-	10/13 mm
К	400 gr	150 gr	300 gr

Y411350-42 - Fully Covering Saddle Pad Yellow

Perfect fit guaranteed with our: Y411350.

Y420250-34 - Inlay Saddle Pad

Perfect fit guaranteed with our: Y420250, Y420330 & Y420333.

Y420336-42 - Inlay Saddle Pad

Perfect fit guaranteed with our: Y420336.

Y411202-45 - Fully Covering Saddle Pad Black

Perfect fit guaranteed with our: Y411202, Y420250, Y420330 & Y420333.

Merchandise Miscellaneous

Y490025 - 2D XL Keychain

JTM120220 - 2D XL Keychain



M120110 - Smart Fast Charger

VEHICLE VOLTAGE INDICATOR 12-24V

• USB-A 3.0 & USB-C Fast charging

Alloy casing

LED light



WINNTEE



Y490010EV - Liftpad EV

An essential piece of equipment for raising cars that need a lifting adaptor. The pad has a 75mm diameter slot that is 15mm deep for compatibility with most brand-specific adapters. It stays on the jack more firmly thanks to magnets on the bottom.

Fits most floor jacks, perfect fit guaranteed with our: Y411202, Y420250, Y420303, Y420330, Y420333, Y420336.





Y490088 - Cap L - XL





Y490033 – Lunch Bag

Y490022 - Backpack XL

- WATERPROOF
- FLOATS ON WATER
- Extra spacious
- 100% PVC





Winntec* is a brand owned by TMG Rechtzaad 6, 4703 RC Roosendaal The Netherlands +31165 561 613 | info@winntec.net

winntec.net



WINNTED

15 cates Californi

